

COLUMN NOTES:


- MAY USE PRECAST CONCRETE PAD IN PLACE OF GRANULAR LEVELING PAD
- FOR COLUMNS TALLER THAN 4' PLACE CONCRETE AND REBAR WITHIN THE COLUMN, AND CONSTRUCT ON A REINFORCED CONCRETE FROST FOOTING. SEE REINFORCED COLUMN INSTALLATION SEQUENCE DETAIL

20" UNREINFORCED COLUMN SECTION

UNREINFORCED COLUMN (4' TALL MAX.)

SCALE: $\frac{3}{4}" = 1'$

THESE PRELIMINARY DETAILS ARE INTENDED AS AN AID IN DESIGNING ATTRACTIVE, DURABLE RETAINING WALLS WITH VERSA-LOK UNITS. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR MATERIAL FOR THE USE CONTEMPLATED, AND ITS MANNER OF USE, IS THE SOLE RESPONSIBILITY OF THE USER. A FINAL PROJECT SPECIFIC DESIGN SHOULD BE PREPARED BY A QUALIFIED, LICENSED, PROFESSIONAL ENGINEER.



VERSA-LOK[®]
Retaining Wall Systems

(800)770-4525 fax(651)770-4089
6348 Hwy36 Ste1, Oakdale, MN 55128 **Solid Solutions[™]**

VERSA-LOK HARMONY DETAILS

20" UNREINFORCED COLUMN SECTION

SCALE:	AS NOTED
DRAWN BY:	PDL
CHECKED BY:	
DATE:	11/2015
DWG. NO.	HAR 20 UNREINF. COLUMN SECT...